




KAYJAY SHARP TRENDYS

Phone : +91-422-2628631
 Mobile: +91-9944973400, +91-9994952700
 Email : sharpump@vsnl.com
 Web : www.sharptrendys.com

Non-Self Priming Pumps



MINI MASTER TRENDY



DEELUXE



MINI DEELUXE

The **Peripheral Non-Self Priming Pumps** are used in domestic overhead tanks, curing at construction sites, pressure system at boosting homes, fountains and small irrigations.



Salient Features

- High quality extruded aluminum body
- Double sealed precision ball bearings with life lubrication
- Fitted with Thermal Overload Protector
- Stainless steel shaft
- Forged brass impeller (electronically balanced)
- Graded cast iron pump casing and motor bearing housing
- Mechanical seal with high alumina seal face
- TEFC capacitor start and run motor
- Single (or) Three phase options
- Capacitor housed in the capacitor box on top of the aluminum body in Deeluxe models
- 1.5 m length extra cord for convenient installation for DEELUXE models

Peripheral – non Self Priming Pumps Specification

S.No	Model		Power kW(HP)	Suction Lift m(ft)	Total Head in Metre								Pipe Size mm(inch)	
	1 Phase	3 Phase			Discharge in Litres / Min								Suction	Delivery
					6	12	18	24	30	36	42	45		
1	MR0SDE	MR0TDE	0.18(0.25)	8(25)	23	18	13	-	-	-	-	-	19(3/4")	19(3/4")
2	MR1SDE	MR1TDE	0.37(0.50)	8(25)	40	30	24	20	15	-	-	-	25(1")	25(1")
3	MR2ST	MR2TT	0.37(0.50)	8(25)	40	30	24	20	15	-	-	-	25(1")	25(1")
4	MR2SD	MR2TD	0.37(0.50)	8(25)	40	30	24	20	15	-	-	-	25(1")	25(1")
5	MR4SD	MR4TD	0.55(0.75)	8(25)	47	44	38	32	26	20	15	-	25(1")	25(1")
6	MR5SD	MR5TD	0.75(1.0)	8(25)	55	49	44	38	32	24	17	14	25(1")	25(1")

SI.No.1 & 2-Mini Deeluxe

SI.No.3 - Mini Mater Trendy

SI.No.4,5 & 6-Deeluxe