



KAYJAY SHARP TRENDYS

Phone : +91-422-2628631

Mobile: +91-9944973400, +91-9994952700

Email : sharpump@vsnl.com

Web : www.sharptrendys.com

OPENWELL SUBMERSIBLE PUMPS



Openwell submersible pump sets are used to lift water from smaller wells, tanks & sumps. The pump set weights less and also it consumes less power. The motor body is made of stainless steel in order to protect them from rusting.

Salient Features

- Rewindable, water cooled motor with stainless steel body
- Dynamically balanced copper stripped rotors with epoxy coated rust proof paint
- Less weight and hence easy for installation
- Higher operating efficiency over wide range of voltage fluctuations and consumes minimum power
- Trouble free operation and require less maintenance due to water lubricated bearings

Openwell Submersible Pump Specification

S.No	Model	Phase	Power kW(HP)	Head in METRE	6	10	15	20	22	25	30	Pipe Size	
												mm	(inch)
												Suction	Delivery
40	JMOW-05J	Single	0.37(0.5)	DISCHARGE IN LPM	102	82	65	30	-	-	-	25(1")	25(1")
41	JMOW-05	Single	0.37(0.5)		135	125	100	65	48	-	-	25(1")	25(1")
42	JMOW-10	Single	0.75(1.0)		230	200	174	130	115	88	-	32(1 1/4")	25(1")
43	JMOW-15	Single	1.1(1.5)		320	290	260	242	200	160	105	32(1 1/4")	25(1")