



**KAYJAY SHARP TRENDYS**

Phone : +91-422-2628631

Mobile: +91-9944973400, +91-9994952700

Email : sharpump@vsnl.com

Web : www.sharptrendys.com

## Self Priming Pumps



SENIOR LITTLE MASTER



LITTLE MASTER TRENDY



MINI DEELUXE



DEELUXE



WONDER SUCTION

The **Peripheral Self Priming Pumps** are used in domestic segment to pump water for overhead tanks, curing at construction sites, pressure boosting system at homes, fountains and small irrigations.

## Salient Features

- High quality extruded aluminum body
- Double sealed precision ball bearings with life lubrication
- Fitted with Thermal Overload Protector
- Stainless steel shaft
- Forged brass impeller (electronically balanced)
- Graded cast iron pump casing and motor bearing housing
- Mechanical seal with high alumina seal face
- TEFC capacitor start and run motor
- Single (or) Three phase options
- Capacitor housed in the capacitor box on top of the aluminum body in Deeluxe models
- 1.5 m length extra cord for convenient installation for DEELUXE models



CM/L - 6001133

**KAYJAY SHARP TRENDYS**

Phone : +91-422-2628631

Mobile: +91-9944973400, +91-9994952700

Email : sharpump@vsnl.com

Web : www.sharptrendys.com

**Peripheral -Self Priming Pumps Specification**

S. No.	Model		Power kW(HP)	Suction Lift M(ft)	Total Head in Metre										Pipe size mm(inch)	
	1 Phase	3 Phase			Discharge In Liters / Minute										Suction	Delivery
					6	12	18	24	30	36	42	45	50	56		
7	MS0SDE	MS0TDE	0.18(0.25)	8(25)	23	18	13	-	-	-	-	-	-	-	19(3/4")	19(3/4")
8	MS1SDE	MS1TDE	0.37(0.50)	8(25)	40	32	24	20	15	-	-	-	-	-	25(1")	25(1")
9	MS2SKJ		0.37(0.50)	8(25)	35	30	20	18	-	-	-	-	-	-	25(1")	25(1")
10	MS2SD	MS2TD	0.37(0.50)	8(25)	40	30	24	20	15	-	-	-	-	-	25(1")	25(1")
11	MS2ST	MS2T	0.37(0.50)	8(25)	40	30	24	20	15	-	-	-	-	-	25(1")	25(1")
12	MS2WS		0.37(0.50)	8(25)	40	32	24	20	15	-	-	-	-	-	25(1")	25(1")
13	MS4SD	MS4TD	0.55(0.75)	8(25)	47	44	38	32	26	20	15	-	-	-	25(1")	25(1")
14	MS5S	MS5T	0.75(1.00)	8(25)	55	49	44	38	32	24	17	14	-	-	25(1")	25(1")
15	MS5SD	MS5TD	0.75(1.00)	8(25)	55	49	44	38	32	24	17	14	-	-	25(1")	25(1")
16	MS5SS	MS5TS	0.82(1.1)	8(25)	65	62	58	52	43	39	31	23	18	10	25(1")	25(1")